



DON & LOW
Nonwovens

Daltex[®] Polypropylene Nonwoven

Product Code U00 (10g/m² - 50g/m²)

Daltex[®] polypropylene spunbond is a nonwoven fabric, thermally bonded using a diamond pattern with a 19% bond area. Daltex[®] polypropylene spunbond is used in a variety of applications offering good strength and abrasion resistance properties.

- Thermally bonded, polypropylene nonwoven fabric
- Wide range of weights, roll widths and lengths
- Different colours and additives available

Technical Data

	Test Method	Units							
Basis Weight	STM 029	g/m ²	10	15	17	20	30	40	50
MD Tensile Strength	STM 030	N	20	30	35	40	70	110	145
CD Tensile Strength	STM 030	N	10	20	23	30	45	75	95
MD Elongation	STM 030	%	70	80	80	90	90	100	110
CD Elongation	STM 030	%	80	90	90	100	100	110	120

MD = machine direction, CD = cross/transverse direction

All products are manufactured under BS EN ISO 9001.



Don & Low reserves the right to change specifications or other product information. Don & Low accepts no responsibility or liability for information provided by third parties. No warranties, express or implied, are offered regarding the suitability of any product for your use, as site conditions and customer requirements vary. Should you require further information, please contact us. Products are sold subject to the seller's terms and conditions of sale. No warranty or immunity is offered against infringement of patents or other intellectual property rights.

©Don & Low Limited, 2009. The intellectual property in the products is owned and protected by Don & Low or its licensors.

Issue 1
August 2009

Don & Low Ltd Nonwovens
Glamis Road, Forfar, Angus DD8 1EY Scotland
Tel: +44 (0)1307 452600 Fax: +44 (0)1307 452610
www.donlow.com

