



DON & LOW
Nonwovens

Daltex[®] Polyethylene Spunbond

Product Code UPE

Daltex[®] UPE is an ultra-soft, polyethylene spunbond nonwoven. Daltex[®] UPE can be used in various medical applications including ostomy, gowns and drapes where softness is important.

- Soft handle and drape
- Available with 19% and 8.5% bond areas
- Gamma or ethylene oxide sterilisable
- Suitable for use in the medical industry
- Material can be sewn, ultrasonic or heat welded
- Available in widths up to 310cm wide
- Standard colours include – Natural, White, Blue, Green and Beige
- Compatible with a range of additives, including UV, anti-static and anti-microbial

Technical Data (based on 19% bond area)

	Test Method	Units					
Basis Weight	STM 029	g/m ²	20	40	60	80	100
MD Tensile Strength	STM 030	N	15	30	45	70	90
CD Tensile Strength	STM 030	N	12	20	25	40	70
MD Elongation	STM 030	%	180	210	240	270	300
CD Elongation	STM 030	%	190	220	250	280	310
Tear Strength	STM 031	N	8	10	15	25	30

MD = machine direction, CD = cross/transverse direction

All products are manufactured under BS EN ISO 9001.



Don & Low reserves the right to change specifications or other product information. Don & Low accepts no responsibility or liability for information provided by third parties. No warranties, express or implied, are offered regarding the suitability of any product for your use, as site conditions and customer requirements vary. Should you require further information, please contact us. Products are sold subject to the seller's terms and conditions of sale. No warranty or immunity is offered against infringement of patents or other intellectual property rights.

©Don & Low Limited, 2011. The intellectual property in the products is owned and protected by Don & Low or its licensors.

Issue 2
August 2011

Don & Low Ltd Nonwovens
Glamis Road, Forfar, Angus DD8 1EY Scotland
Tel: +44 (0)1307 452600 Fax: +44 (0)1307 452610
www.donlow.com

